

# HARVIA CILINDRO

HPC700400

The Harvia Cilindro electric heater contains a massive amount of stones. Thanks to the grate-like outer shell, each bather can adjust the nature of the steam: soft when throwing water onto the side of the heater and sharp when throwing water straight on top of the stone pillar. Cilindro is impressive to both look at and experience.

## Advantages

- Contains a massive amount of stones that provides soft yet strong heat
- Outer surface made of stainless steel
- With integrated timer and thermostat



## Features

Main material : Steel


H x W x D : 930.0 x 320.0 x 320.0 mm

Net weight (kg) : 10.0

Installation location : Floor

ID	GTIN	Output (kW)	Sauna room size min - max m3
HPC700400	6410082610068	6.8 kW	6.0-10.0

## Related products




HPC1



HPC2



HPC3



HPC3L



HPC2L

## Spare parts

Product	ID	Pcs
Heating element 2260W/230V Figaro	ZRH-720	3
Contactora K1 62.83.8.230.0300	WX207	1
Sensor with reset button 125 degr.	WX248	1
Timer 4h+8h	ZSK-510	1
Thermostat/overheating limiter switch	ZSK-520	1
Thermostat knob	ZST-220	1
Timer knob	ZST-230	1
Upper triangle support Cilindro	ZSC-135	1
Support plate for heating elements	ZSC-140	1
Bracket for capillary sensor	ZSC-145	1

## Technical details

Technical data	Type / attribute	HPC700400
	Color	Stainless Steel
	Power output	6.8 kW
	Stone sizes	Ø5-10 cm
	Stone amount (kg)	80
Dimensions	Product width	320
	Product height	930
	Product depth (mm)	320
	Net weight (kg)	10
	Gross weight	11.4
	Package width	330
	Package height	975
	Package depth	330
Safety and installation dimensions	Safety distance front (non-combustible materials)	100
	Safety distance front (combustible materials)	100
	Safety distance right side (combustible materials)	100
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	100
	Safety distance left side non-combustible materials	100
	Safety distance side (non-combustible materials)	100
	safety distance to the side wall (combustible materials)	100
	Safety distance behind (non-combustible materials)	100
	Safety distance behind (combustible materials)	100
	Safety distance (Ceiling)	950
	Room min. height(depends on connections and therefore from output, star/delta)	1900
	Installation opening height	1900
	Installation opening width	520
Installation opening depth	520	